

UL Product iQ

UL'S NEXT GENERATION CERTIFICATIONS SEARCH The same trusted data in a modern search engine.

NOW AVAILABLE

LEARN MORE

EQQY2.MH16060 Casting Impregnation Materials - Component

Page Bottom

Casting Impregnation Materials - Component

See General Information for Casting Impregnation Materials - Component

GODFREY & WING INC MH16060

220 CAMPUS DR AURORA, OH 44202-6663 USA

Casting impregnation material, 95-1000 for exposure to gasoline, kerosene, fuel oils, naphtha, gasoline-ethanol and gasoline-methanol mixtures with a maximum of 15 percent ethanol or methanol.

Casting impregnation material, 95-1000A for exposure to gasoline, kerosene, fuel oils, naphtha, gasoline-ethanol and gasoline-methanol mixtures with a maximum of 15 percent ethanol or methanol, LP-gas and Natural Gas.

Casting impregnation material, 95-1000AA for exposure to gasoline, kerosene, fuel oils, naphtha, LP-gas and Natural Gas.

Marking: Company name and material designation.

Last Updated on 2015-05-13

<u>Questions?</u> <u>Print this page</u> <u>Terms of Use</u> <u>Page Top</u>

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".